## ORWAK FLEX 5010-E

The ORWAK FLEX 5010-E is a small but tough baler, that requires little space but offers effective compaction. The unit is sturdy, reliable and easy to operate.







SMALL FOOTPRINT

BALE WEIGHT

## **ORWAK BENEFITS**





#### **MORE PRODUCTIVE USE OF TIME**

Less time spent on waste handling, more time for your core activities!

### MORE SPACE & ORDER

Our balers rapidly minimize the space the waste takes up, keeping aisles free and tidy.

#### LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced  ${\rm CO_2}$  emissions. Sorting at source yields a higher quality of waste material for recycling.

### WHY ORWAK FLEX?

- Versatile compaction for many different application areas
- Hygienic and safe compaction and disposal of mixed or hazardous waste
- Special solutions for special needs



# ORWAK FLEX 5010-E

### Small but tough

#### **TOP LOADING**

Feeding material into this top-loading baler is fast and convenient, and the compaction ratio is impressive thanks to high pressure on a small surface.

#### **VERSATILE**

The design means that the compactor is versatile and can be used for baling waste products such as cardboard, paper, plastic and even thin wood packaging.

#### **COMPACT DESIGN**

Thanks to its compact design, the baler fits where you need it to be and is easy to install in any location.

#### **BALE TROLLEY INCLUDED**

Model 5010-E is always delivered with a bale trolley for effortless baling and smooth internal transportation of the bale.



## ORWAK FLEX5010-E IS OPTIMIZED FOR:

#### **PAPER**

- Cardboard
- Shredded paper
- Paper sacks

#### **PLASTIC FOIL**

- Shrink film
- Plastic bags

#### OTHER METALS

Metal straps


#### **OTHER PLASTICS**

■ Plastic straps

**DIMENSIONS & SPECIFICATIONS** 

DIMENSIONS										
Α	В	С	D	E						
2140 mm	910 mm	1110 mm	1820 mm	1295 mm						

ENERGY CONSUMTION						
STANDBY MODE	MAXIMUM OPERATION ONE HOUR					
	660 W/H					



TECHNICAL SPECIFICATIONS											
LOADING APERTURE	CYCLE TIME	PRESS FORCE	BALE SIZE	BALE WEIGHT	MACHINE WEIGHT	NOISE LEVEL	PROTECTION CLASS	OPERATING POWER			
Width:: 700 mm Depth: 500 mm	36 secs	3 ton, 30 kN	Width: 700 mm Depth: 500 mm Height: 700 mm	Cardboard: Up to 60 kg Plastic: Up to 80 kg	370 kg	70 db (A)	IP 55	Single Phase 230 V, 50 Hz, 10 A			

 $We reserve the {\it right to make changes to specifications without prior notice.} \textit{Bale/bag/bin weights are dependent upon material type}$ 

#### **ORWAK AB**

Svetsaregatan 4 S-576 33 Sävsjö SWEDEN Tel: +46-(0)382-15700 info@orwak.com

